



# Discreet Wall Heater

## FBG Series

### Features

#### Color

- Standard: white.

#### Finish

- Standard: epoxy/polyester powder paint.

#### Voltage

- 240/208V, 1-phase.

#### Construction

- 20-gauge steel cabinet.
- Warm air outlet that directs the air downwards, towards the center of the room.
- Bar grille prevents insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- Manual de-energize high-limit temperature control.

#### Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated motor.

#### Heating element

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

#### Control

- Line voltage control circuit for thermostat, timer or switch (not included, must be compatible with the selected voltage and wattage of the heater).

*Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.*

#### Installation

- Recommended installation height: max. 10 ft. (3 m), min. 6 ft. (1.8 m).
- Wattage must be selected at the time of wiring (750W or 1500W).
- Quick surface-mounted installation, with the included mounting bracket.
- Flexible cable with electrical wall box cover plate included.
- Requires installation of a wall electrical box, not supplied.

#### Warranty

- 2-year against defects.
- 5-year on the heating element.

#### Application

- Bathroom, entrance way, stairwell.

### Model

Product #	Watts <sup>1</sup> 240/208V	Net Weight		Gross Weight		Packaging Dimensions					
		lb	kg	lb	kg	A in.	A mm	B in.	B mm	C in.	C mm
FBG1500BL	750/563 1500/1125	9	4	9.5	4.3	13.3	338	8.75	222	6	152

<sup>1</sup>Wattage must be selected when installing (750W or 1500W).  
Standard color is white.

