



Compact Wall Heater

VSG Series

Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.

Finish

- Standard: epoxy/polyester powder paint.

Tension

- 240/208V, 1 phase.

Construction

- 20-gauge steel cabinet.
- 22-gauge steel front cover.
- High-limit temperature control with automatic reset.

Fan

- Quiet fan operating.
- 240/208V models: 500W to 1000W; 40 cfm fan and 1250W to 2000W; 80 cfm fan.
- Factory-lubricated motor.

Heating element

- 240/208V: durable tubular heating element with fins.

Control

- Built-in thermostat available with a control knob.
- If an electronic thermostat is used, it must be compatible with forced-air heaters.

Installation

- Wall installation only.
- The air outlet should be installed at least 4 in. (102 mm) from flooring, 10 in. (254 mm) from linoleum flooring.
- Quick installation with recess box mounting holes.
- Large wiring compartment.
- May be recessed in 2 in. X 3 in. stud partitions.
- Surface mounting box available.
- Tight fit with V-shaped recess box.

Warranty

- 5-year against defects.

Application

- Entrance way, kitchen, bathroom, family room, basement.

Models

Product #	Watts 240/208V	Net Weight		Gross Weight		Packaging Dimensions					
		lb	kg	lb	kg	A		B		C	
						in.	mm	in.	mm	in.	mm
VSG0500BL	500/375	7.2	3.3	7.9	3.6	17	432	8.5	216	4 1/2	114
VSG1000BL	1000/750	7.2	3.3	7.9	3.6	17	432	8.5	216	4 1/2	114
VSG1500BL	1500/1125	7.2	3.3	7.9	3.6	17	432	8.5	216	4 1/2	114
VSG2000BL	2000/1500	7.2	3.3	7.9	3.6	17	432	8.5	216	4 1/2	114

Options

Product #	Description
KIT-VSG-TB6	Single-pole bi-metal thermostat, with a control knob
KIT-VSG-TB26 ¹	Double-pole bi-metal thermostat, with a control knob
KIT-VSG-BSBL	Surface mounting box

¹ "Off" position.
Standard color is white.
Upcharge available for optional colors shown in the color chart section.

Mounting positions available.
Pictures showing front panel. Directional vane air flow.

